

Rainfresh Drinking Water Filter
Model – IM100



PERFORMANCE DATA SHEET

This system has been tested according to NSF/ANSI 42 for reduction of the substances listed below in Table I. The concentration of the indicated substances in the water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI 42.

Contaminant	Influent Challenge Concentration	Reduction Requirement	Average Reduction Efficiency
<i>Standard 42 – Aesthetic Effects.</i> Taste, Odour, Chlorine Reduction	2.0 mg/L ± 10%	≥ 50%	> 98%

TABLE- I

The standards referenced above evaluate performance for use with disinfected water.
 All testing performed under standard laboratory conditions. Actual performance may vary.

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system
 Contaminants reduced by this filter are not necessarily present in water. Individuals requiring water of specific microbiological purity should follow the advice of their doctor or local health unit.

Technical Specifications

- Filter cartridge model - IM100 or Ice-maker Filter
- Rated cartridge life - 6 to 12 months or 1000 US Gal (3785 L)
- Rated service flow - 0.5 US GPM (1.89 LPM)
- Inlet/Outlet connections - ¼" FNPT.
- Operating Temperature - 4°C (39°F) minimum to 38°C (100°F) maximum.
- Max. operating Pressure - 100 psi (689 kPa) max.

General Operation & Maintenance: See product manual for maintenance instructions. User is responsible for general maintenance.

Warranty – Limited 5 year warranty. See product manual for details.

For replacement parts contact your nearest Rainfresh dealer.



Envirogard Products Limited
 446, Major Mackenzie Drive East, Richmond Hill,
 ON L4C 1J2, CANADA
 Tel: (905) 884 9388 Fax: (905) 884 3532.
 Web: www.rainfresh.ca