

FC250

Undersink or Inline Drinking Water System



Rainfresh FC250 Drinking Water System is designed to deliver better quality drinking water at a fraction of the cost of bottled water. It removes chlorine, sediment, taste and odour and can be installed either undersink or inline to serve 1 or 2 drinking water outlets. FC250 is ideal for homes, cottage/cabins, farms, offices, boats or RV.



Performance

Reduces

- > 95% Chlorine
- sediment down to 5µ nominal
- Taste and odour

Install undersink or inline to serve 1-2 drinking water outlets

Features

1) Built-in Bypass Valve & Pressure Relief

FC150 also features a built-in shut-off and bypass valve. By simply rotating the top valve, the filter can be either by-passed or shut-off with automatic pressure relief



Built-in On / Off / Bypass Valve -
Simplifies installation and operation.



No Mess -
Head and sump reservoirs prevent sprays and spills.

Transparent Sump -
See your filter working!

No Wrench Required -
1/8th turn bayonet closure allows effortless cartridge changes.



2) Easy-open Housing – No Wrench Required !

The FC150 features Rainfresh’s unique easy-open filter housing that does not require the use of a filter wrench. Simply grab the sump and turn 1/8th clockwise to open the sump, without using any tools.

3) Transparent Sump – See your filter working!

The clear transparent sump allows you to see the filter condition without turning the water off.



Installation Notes:

Unit Width (Inch)	Unit Height (Inch)	Unit Depth (Inch)	Connections
4.75"	13.75"	4.75"	3/4" Female NPT

- Connector kits for inline installation (CK2) & undersink installation (CK3) sold separately
- Not recommended for whole house installation

Specifications:

- Water Temperature Range : 4 °C to 37 °C (39 to 100 °F)
- Feed Water Pressure : 20 to 100 psi* (137 to 689 KPa; 1.37 – 6.89 bar)
- Flow Rate – 0.75 US GPM (2.8 LPM)
- BPA-free materials

Replacement Cartridge: Model CF2 – 5 micron (included). Optional cartridge model CA1 for chloramine & chlorine reduction

Replacement Frequency: 1,000 US gal (3,785 L), or once every 6 months**

* -If water pressure exceeds the rated pressure, a pressure regulator & water hammer arrestor must be installed before the filter housing. It is recommended that the pressure regulator be set at 75 psi or less. ** - Cartridge life is directly dependent on water conditions. High sediment levels or water use may cause more frequent replacement

5 year limited warranty



Tested & certified by CSA International to NSF/ANSI 42 and to CSA B483.1



Sep 2011



Envirogard Products Limited

446 Major Mackenzie Drive East, Richmond Hill, ON L4C 1J2, CANADA

Toll Free: 1800-667-8072 ; Tel: 001.905 884 9388

Fax: 001.905.884 3532 ; E-Mail : info@rainfresh.ca

Web: www.rainfresh.ca